



# GNSS Receiver

**Renowned partners**

Partnering with the high-quality brands SATEL and NovAtel, this antenna enables you to reduce your failure rates and increase your productivity.

**Open & flexible configuration**

The Zenith Manager, a stand-alone application available for Windows and Android™ operating systems, enables you to configure your antenna without using the field controller.

**Affordable price**

Providing top-performing technology and an affordable price, the Zenith16 convinces with a remarkable performance ratio.

**Seamlessly integrated into your workflow**

X-PAD Ultimate's intuitive interface allows everyone to easily perform surveying and construction tasks. X-PAD Office Fusion allows direct integration and managing with different types of data in one software.





### Receiver specifications

Q-Lock Pro™ functionality	Lowest noise and advanced multipath mitigation for highest reliability
Reliability	99.99%
Measurement Engine	NovAtel OEM7, 181 channels, dual-frequency / multi-constellation
GPS tracking	L1, L2, L2C
GLONASS tracking	L1, L2, L2C
BeiDou tracking	B1, B2 (opt)
Galileo tracking	E1, E5b (opt)
QZSS tracking	L1, L2C (opt)
Positioning rate	5 Hz
SBAS	EGNOS, WAAS, MSAS, GAGAN

### Receiver accuracy (rms)\*

RTK	Hz	10 mm + 1 ppm
	V	20 mm + 1 ppm
Network RTK	Hz	10 mm + 0.5 ppm
	V	20 mm + 0.5 ppm
Static	Hz	5 mm + 0.5 ppm
	V	10 mm + 0.5 ppm
Static - long	Hz	3 mm + 0.1 ppm
	V	3.5 mm + 0.4 ppm

\* Measurement precision, accuracy, reliability and time for initialisation are dependent upon various factors including number of satellites, observation time, atmospheric conditions, multipath etc. Figures quoted assume normal to favourable conditions. A full BeiDou and Galileo constellation will further increase measurement performance and accuracy.  
 \*\* Depending on device configuration; w/o battery

### Interfaces

Keyboard	On/off and function key
LED status indicators	Position, battery, Bluetooth®, RTK receive, RTK transmit, data storage
LED mode indicators	Rover, base, static
Data recording	Removable microSD card

### Communication

UHF radio module	SATEL, 500mW, 1000 mW transceiver, 403–473 MHz; (opt)
Bluetooth®	Device class II QR-iConnect functionality
TNC connector	High sensitivity, UHF antenna
Communication port	USB, serial & power

### Physical specifications

Dimensions	Height 95 mm, ø 198 mm
Weight	1.09 - 1.13 kg **
Operating temp.	-40°C to 65°C
Environmental protection	IP68/ IP66/ MIL
Humidity	100%, condensing
Vibration	Mechanical stress resistant according to ISO 9022-36-05
Shock	Withstands 2 m drop onto hard surface

### Power supply

Internal battery	Removable, Li-Ion 2.6 Ah / 7.4 V
Operating time	9 h in static / 6 h in rover mode
External power	10.5 V to 28 V, LEMO® plug



1019 - 875288 en Copyright GeoMax AG.

Illustrations, colours, product offerings, descriptions and technical specifications are not binding and may change without notice. All trademarks and trade names are those of their respective owners.



Learn more at:  
[geomax-positioning.com](http://geomax-positioning.com)

GEOMAX AUTHORISED DISTRIBUTION PARTNER